



PTP/CLIENT ANTENNA

WiBOX PA 24-19

WiBOX PA 24-19 is a panel antenna (SISO) operating at the frequency band of: 2.4 – 2.5 GHz with 19 dBi gain, in horizontal or vertical polarization (changeable on the front cover). The antenna can be used in point-to-point (PTP) topology for medium distance links as bridges, backbones, or as a client antenna. It can work indoor and outdoor (IP 67). It works with the systems of: WLAN (802.11b/g). The antenna is integrated with the top quality WiBOX Large box system.











Electrical specification

Frequency	2.4 - 2.5 GHz
Gain	19 dBi
VSWR	<2.00
Beamwidth	16°/16°
Polarization	V,H
Cross-Polar Isolation	
Front-to-Back	
Separation between Connectors	
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	39.2 x 39.6 x 9.9 cm 15.43 x 15.59 x 3.9 inch
Weight	2.73 kg
Connector	RJ45
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mast Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- Gain for the frequency of 2400 2500 MHz 0x 19 dBi
- > Polarization V,H for the frequency of 2400 - 2500 MHz
- > 0 x Connector SMA
- Big, ergonomic and voluminous WiBOX Large enclosure for radio equipment installation
- Outdoor Waterproof Enclosure WiBOX Large
- Designed and resistant for any weather conditions
- > RJ45 Waterproof System
- Grounding system protecting against lighting - DC Ground
- > 36 Warranty Months


Systems

- > LTE band 40, 41, 53
- > WLAN 2.4 GHz
- > WiMAX 2.3 GHz, 2.5 GHz
- > RFiD 2400 2483 MHz
- > Bluetooth 2400-2483 MHz
-) ISM 2400-2483 MHz


Applications

- > PtP connections
- > PtM Connections
- System Integration

Plots



Radiation pattern Pol 1



Radiation pattern Pol 2