



HIGH-DENSITY DUAL BAND BASE SECTOR ANTENNA

WiBOX SA M3DBC245-120-8V

Wireless Instruments three element **MIMO 3x3 2.4/5 GHz dual-band** antenna for Wi-Fi is rugged and high-performance panel for outdoor and indoor applications. **WiBOX SA M3DBC245-120-8V** is 3-Element Patch Antenna predicted mainly for high-density installations where high gain and wide beamwidth is required. The system offers relatively high gain with wide horizontal beam and low F/B ratio, which makes it unique solution on the market. The antenna is designed to work with 2.4-GHz/5-GHz Access Points (like Cisco, Aruba, Huawei and others), offers IP67 for whole system and No. 3 of RP-SMA/U.FL/MMCX pigtailed located in the installation box. The antenna is integrated with **WiBOX Medium** enclosure by Wireless Instruments which offers the installation compartment for electronic stuff. **WiMount** mounting system which comes with the antenna enables wall or mast mounting.

ROHS



Electrical specification

Frequency	<ul style="list-style-type: none"> ⊗ 2.4 - 2.5 GHz ⊗ 4.6 - 6.4 GHz
Gain	<ul style="list-style-type: none"> ⊗ 8 dBi ⊗ 7 dBi ±1
VSWR	<ul style="list-style-type: none"> ⊗ <1.60, max < 1.80 ⊗ <1.60, max < 1.80
Beamwidth	<ul style="list-style-type: none"> ⊗ 120°/60° ⊗ 120°/90°
Polarization	<ul style="list-style-type: none"> ⊗ V ⊗ V
Cross-Polar Isolation	>25 dB
Front-to-Back	<ul style="list-style-type: none"> ⊗ > 20 dB ⊗ > 20 dB
Separation between Connectors	
Impedance	50 Ω
Max Input Power	20 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	27.2 x 27.6 x 9.6 cm 10.71 x 10.87 x 3.78 inch
Weight	1.8 kg
Connector	RJ45 & 1xSMA/SMA RP/TNC RP/MMCX
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mast Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- ▶ Gain for the frequency of 2400 - 2500 MHz 1x 8 dBi
- ▶ Polarization V for the frequency of 2400 - 2500 MHz
- ▶ Gain for the frequency of 4600 - 6400 MHz 1x 7 dBi ±1
- ▶ Polarization V for the frequency of 4600 - 6400 MHz
- ▶ 1 x Connector SMA/SMA RP/TNC RP/MMCX
- ▶ Big, ergonomic and voluminous **WiBOX Medium** enclosure for radio equipment installation
- ▶ Outdoor Waterproof Enclosure **WiBOX Medium**
- ▶ Designed and resistant for any weather conditions
- ▶ RJ45 Waterproof System
- ▶ Grounding system protecting against lightning - DC Ground
- ▶ 36 Warranty Months

Systems

- ▶ LTE band - 40, 41
- ▶ WLAN - 2.4 GHz, 5 GHz
- ▶ WiMAX - 2.3 GHz, 2.5 GHz, 5 GHz
- ▶ RFID - 2400 - 2483 MHz, 5725 - 5875 MHz
- ▶ Bluetooth - 2400-2483 MHz
- ▶ ISM - 2400-2483 MHz, 5725-5875 MHz

Applications

- ▶ Stadiums, Public Places
- ▶ Hotspot
- ▶ PtM Connections
- ▶ System Integration