



TRIPLE BAND PTP/CLIENT ANTENNA

WiPanel LTE M4MB0727-4V, MIMO 4x4, 5m SMA

WiPanel LTE M4MB0727-4V directional MIMO 4x4 antenna is predicted for 4G LTE high categories from cat 5 up to cat 19. The antenna improves the signal in rural/suburban and locations where the mobile signal is weak. That antenna is predicted to be installed on the buildings (on the pole or on the wall). Due to very wide working frequency range, the antenna is universal client for LTE bands like LTE700/800/1800/1900/2100/2300/2600. It's compatible with all MIMO 4x4 LTE modems and routers working in categories: cat 5, cat 6, cat 7, cat 9, cat 10, cat 11, cat 12, cat 13, cat 15, cat 16, cat 18, cat 19, cat 20.

ROHS



Electrical specification

Frequency	0.694 - 0.96 GHz 1.7 - 2.2 GHz 2.2 - 2.7 GHz
Gain	4 dBi 5 dBi 6 dBi
VSWR	<1.30, max < 1.80 <1.30, max < 1.80 <1.30, max < 1.80
Beamwidth	90°/90° +/- 30° 90°/90° +/- 30° 90°/90° +/- 30°
Polarization	V V V
Cross-Polar Isolation	
Front-to-Back	
Separation between Connectors	
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	27.2 x 27.6 x 9.6 cm 10.71 x 10.87 x 3.78 inch
Weight	1.8 kg
Connector	4xSMA
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 75°C from -40°F to 167°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Most Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- Gain for the frequency of 694 - 960 MHz 4x 4 dBi
- Polarization V for the frequency of 694 - 960 MHz
- Gain for the frequency of 1700 - 2200 MHz 4x 5 dBi
- Polarization V for the frequency of 1700 - 2200 MHz
- Gain for the frequency of 2200 - 2700 MHz 4x 6 dBi
- Polarization V for the frequency of 2200 - 2700 MHz
- 4 x Connector SMA
- Big, ergonomic and voluminous **WiBOX Medium + 4x SMA** enclosure for radio equipment installation
- Outdoor Waterproof Enclosure **WiBOX Medium + 4x SMA**
- Designed and resistant for any weather conditions
- Grounding system protecting against lightning - DC Ground
- 36 Warranty Months

Systems

- LTE band - 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 23, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 53, 65, 66, 67, 68, 69, 70, 85
- WiMAX - 2.3 GHz, 2.5 GHz, 700 MHz
- 3G - 2100 MHz, 850 MHz, 900 MHz
- GSM - 1800 MHz, 1900 MHz, 850 MHz
- RFID - 2400 - 2483 MHz, 865 - 868 MHz, 902 - 928 MHz
- ISM - 2400-2483 MHz, 868-870 MHz
- WLAN - 2.4 GHz
- Bluetooth - 2400-2483 MHz